Conductor Stranding Material	Core	Shield	Jacket	DCR COnductor	DCR Shield	Nominal Impedance	Nominal Capacitance	Nom. Vel. Of Prop.	Screening Factor	Nominal Attenuation dB/100meters							Temp. Range	Cable Weight	Max.Pull Tension	Min. Bend Radius
ø mm	ø mm	First	ø mm	Ω/km	Ω/km	Ω/km	pF/m	%	dB	MHz	MHz	MHz	MHz	MHz	MHz	MHz				
Material	Material	Second	Material						%	dB	dB	dB	dB	dB	dB	dB				

04PB-002-00 Draka

75Ω Miniature SDI Video Cable

0.6 mm Ø Solid Bare Copper Conductor, Gas-injected foam PE insulation, Aluminum Foil and Tinned Copper Braid Shield, PVC Jacket.

0.6	2.8	Al Foil	4.5							1	3	5	10	30	100	200	-40°C to +75°C	27 Kg/Km	60 N	25 mm
Solid	Gas	Tinned								1.2	1.9	2.5	3.5	5.9	10.5	15				
Bare	Injected	Copper	PVC	61	17	75	56	78	≥100	300	500	800	1000	1500	3000	5000				
Copper	PE	Braid								18.7	24.5	31.5	35.5	43.2	63.6	88.1				

02PB-202-00 BELDEN

75Ω Miniature SDI Video Cable (1855A)

0.58 mm Ø Solid Bare Copper Conductor, Gas-injected foam PE insulation, Aluminum Foil and Tinned Copper Braid Shield, PVC Jacket.

0.58	2.59	Al Foil	4							1	3.6	10	71.5	135	270	360	-30°C to +75°C	26 Kg/Km	160 N	38 mm
Solid	Gas	Tinned								1.3	2.6	3.9	10	12.5	18	20.3				
Bare	Injected	Copper	PVC	66	25	75	53.5	83	-	540	720	1000	1500	2250	3000	-				
Copper	PE	Braid								25.3	31.5	34.5	43.0	52.5	60.7	-				

04PB-007-00 Draka

75Ω SDI Video Cable

0.8 mm Ø Solid Bare Copper Conductor, Gas-injected foam PE Insulation, Aluminum Foil and Tinned Copper Braid Shield, PVC Jacket.

0.8	3.7	Al Foil	5.9							1	3	5	10	30	100	200	-40°C to +75°C	49 Kg/Km	100 N	40 mm
Solid	Gas	Tinned								0.9	1.5	1.9	2.7	4.4	7.9	10.9				
Bare	Injected	Copper	PVC	35	10	75	56	78	≥100	300	500	800	1000	1500	3000	5000				
Copper	PE	Braid								13.3	17.6	22.8	25.5	31.3	46.5	65.3				

02PB-202-00 BELDEN

75Ω SDI Video Cable (1505A)

0.81 mm Ø Solid Bare Copper Conductor, Gas-injected foam PE Insulation, Aluminum Foil and Tinned Copper Braid Shield, PVC Jacket.

0.8	3.68	Al Foil	5.9							1	3.6	10	71.5	135	270	360	-30°C to +75°C	46 Kg/Km	209 N	63.5 mm
Solid	Gas	Tinned								1.0	1.9	2.9	6.9	8.9	12.5	14.4				
Bare	Injected	Copper	PVC	32.8	12.5	75	53.5	83	-	540	720	750	1000	1500	2250	3000				
Copper	PE	Braid								18.0	21.0	21.3	24.9	30.5	38.06	44.0				

04PB-009-00 Draka

75Ω SDI, HDTV Video Cable

1.0 mm Ø Solid Bare Copper Conductor, Gas-injected foam PE Insulation, Aluminum Foil and Tinned Copper Braid Shield, PVC Jacket.

1.0	4.8	Al Foil	7.0							1	3	5	10	30	100	200	-40°C to +75°C	69 Kg/Km	140 N	45 mm
Solid	Gas	Tinned								0.8	1.3	1.6	2.1	3.5	6.2	8.9				
Bare	Injected	Copper	PVC	22	7	75	56	78	≥100	300	500	800	1000	1500	3000	5000				
Copper	PE	Braid								11.3	14.8	18.5	20.7	24.9	37.3	55.1				

02PB-208-00 BELDEN

75Ω SDI, HTDV Video Cable (1694A))

1.0 mm Ø Solid Bare Copper Conductor, Gas-injected foam PE Insulation, Aluminum Foil and Tinned Copper Braid Shield, PVC Jacket.

1.0	4.57	Al Foil	6.99							1	3.6	10	71.5	135	270	360	-30°C to +75°C	61 Kg/Km	306 N	70 mm
Solid	Gas	Tinned								0.8	1.5	2.4	5.2	6.9	9.7	11.3				
Bare	Injected	Copper	PVC	28	9.2	75	53.1	83	-	540	720	750	1000	1500	2250	3000				
Copper	PE	Braid								13.9	16.1	16.4	19.3	24.0	30.0	35.0				

NEUTRIK CONNECTING THE WORLD · Telegärtner · BELDEN · ADC · SCHILL · Littlite USA · Draka · NTi AUDIO · K&M KÖNIG & MEYER Stands For Music · Prolink-AV™

promedia
22 67021711 • 22 26354891 email: info@promediain.net