Conductor Stranding Material	Core	Shield	Jacket	DCR COnductor	DCR Shield	Nominal Impedance	Nominal Capacitance	Nom. Vel. Of Prop.	Screening Factor	Nominal Attenuation dB/100meters							Temp. Range	Cable Weight	Max.Pull Tension	Min. Bend Radius
ø mm	ø mm	First	ø mm	Ω/km	Ω/km	Ω/km	pF/m	%	dB	MHz	MHz	MHz	MHz	MHz	MHz	MHz				
Material	Material	Second	Material						%	dB	dB	dB	dB	dB	dB	dB				

04PB-176-00 Draka

75Ω HD-PRO Miniature HDSDI Video Cable

0.6 mm Ø Solid Bare Copper Conductor, Gas-injected foam PE Insulation, Aluminum Foil and Tinned Copper Braid Shield, PVC Jacket.

0.6	2.8	Al Foil	4.5							1	3	5	10	30	100	200	-40°C to +75°C	28 Kg/Km	60 N	25 mm
Solid	Gas	Tinned								1.2	1.9	2.5	3.5	5.9	10	14.1				
Bare	Injected	Copper	PVC	61	17	75	56	78	≥100	300	500	800	1000	1500	3000	5000				
Copper	PE	Braid								17.8	24	29.7	33.2	39.6	60.9	78.9				

04PB-177-00 Draka

75Ω HD-PRO HDSDI Video Cable

0.8 mm Ø Solid Bare Copper Conductor, Gas-injected foam PE Insulation, Aluminum Foil and Tinned Copper Braid Shield, PVC Jacket.

0.8	3.7	Al Foil	5.9							1	3	5	10	30	100	200	-40°C to +75°C	49 Kg/Km	100 N	40 mm
Solid	Gas	Tinned								0.9	1.5	1.9	2.7	4.4	7.9	10.9				
Bare	Injected	Copper	PVC	35	10	75	56	78	≥100	300	500	800	1000	1500	3000	5000				
Copper	PE	Braid								13.3	17.6	22.8	25.5	30.6	46.5	65.3				

04PB-178-00 Draka

75Ω HD-PRO HDSDI Video Cable

1.0 mm Ø Solid Bare Copper Conductor, Gas-injected foam PE Insulation, Aluminum Foil and Tinned Copper Braid Shield, PVC Jacket.

1.0	4.8	Al Foil	7.0							1	3	5	10	30	100	200	-40°C to +75°C	69 Kg/Km	140 N	45 mm
Solid	Gas	Tinned								0.8	1.3	1.6	2.1	3.5	6.2	8.9				
Bare	Injected	Copper	PVC	22	7	75	56	78	≥100	300	500	800	1000	1500	3000	5000				
Copper	PE	Braid								11.3	14.8	18.5	20.7	24.9	37.3	55.1				

04PB-009-00 Draka



75Ω HDSDI Video Cable

1.6 mm Ø Solid Bare Copper Conductor, Gas-injected foam PE Insulation, Aluminum Foil and Tinned Copper Braid Shield, PVC Jacket.

1.6	7.3	Al Foil	10.3							1	3	5	10	30	100	200	-40°C to +75°C	69 Kg/Km	140 N	45 mm
Solid	Gas	Tinned								0.4	0.7	0.9	1.3	2.2	3.9	5.3				
Bare	Injected	Copper	PVC	9.5	4.3	75	56	78	≥100	300	500	800	1000	1500	3000	5000				
Copper	PE	Braid								7	9.2	11.8	13.2	16.9	26.4	41.3				

04PB-180-10 Draka

75Ω HI-FLEX SDI Video Cable

0.8 mm Ø Stranded Bare Copper Conductor, Gas-injected foam PE Insulation, Two layers of Tinned Copper Braid Shield, PVC/Rubber Jacket.

0.8	3.7	TC Braid	5.9							1	10	100	200	300	500	800	-40°C to +75°C	49 Kg/Km	100 N	60 mm
Stranded	Gas	Tinned								1	2.9	8.4	11.6	14.1	18.6	24.2				
Bare	Injected	Copper	PVC/	50	10	75	56	78	≥90	1000	1500	2250	3000	3500	4000	5000				
Copper	PE	Braid	Rubber							27	33.9	44.1	51.9	57.4	60.2	71.1				

04PB-181-10 Draka

75Ω HD-PRO HDSDI Video Cable

1.0 mm Ø Stranded Silver Coated Copper Conductor, Gas-injected Foam PE Insulation, Two layers of Tinned Copper Braid Shield, PVC/Rubber Jacket.

1.0	4.8	TC Braid	7.0							1	10	100	200	300	500	800	-40°C to +75°C	80 Kg/Km	115 N	45 mm
Stranded	Gas	Tinned								0.5	1.9	8	10.1	14	17.3	22				
Silver Coated	Injected	Copper	PVC	21	5	75	56	67	≥90dB	1000	1500	2250	3000	3500	4000	5000				
Copper	PE	Braid								25.8	32	41.6	49	54.4	57.1	67.1				

NEUTRIK CONNECTING THE WORLD · Telegärtner · BELDEN · ADC · Schiff · Littlite USA · Draka · NTi AUDIO · K&M KÖNIG & MEYER Stands For Music · Prolink-AV™

promedia
22 67021711 • 22 26354891 email: info@promediain.net